

# ADHESIVE TAPES





## THE COMPANY

Located in northern Spain (Basque Country), with more than 50 years of experience serving the industry, we are one of Europe's main manufacturers, exporting to more than 70 countries.

Our facilities, with a surface area of more than 36.000m<sup>2</sup>, the experience and knowledge of our workers (>180), continuous investment in state-of-the-art machinery, the constant improvement of our production facilities, etc., make it possible for us to produce a wide range of adhesive tapes designed to meet increasingly demanding market needs at all times.

## SUSTAINABILITY

At Ubis, we are committed to the future and the environment. That is why we invest in the improvement of our production processes by means of the application of the BAT (Best Available Technology) for the sector, making possible the use of more sustainable raw materials, thus creating less environmental impact, and providing our clients with sustainable packaging solutions.

We also have an energy-saving programme, water management systems, classification processes and waste-recycling.

In short, we focus on carrying out sustainable activity with a view to preserving natural resources, supplying the market with our new Ubis Ecoline range.

PACKAGING

PVC



Did you know this about our PVC tapes?

- The PVC tapes adhesive is produced using natural rubber that is obtained from sustainably harvested “hevea brasiliensis” trees on plantations/farms.
- Around 98% of the solvent used is recovered and reused in the production process. This is achieved by using the Best Available Technology (BAT) for the sector in Europe.

PRODUCT	BACKING	ADHESIVE	BACKING THICKNESS (MIC)	TOTAL THICKNESS (MIC)	ADHESION (N/CM)	TENSILE STRENGTH (N/CM)	ELONGATION AT BREAK (%)	COLOUR
PVC 240	PVC	NATURAL RUBBER	32	49	2,4	47	75	BROWN, TRANSPARENT AND WHITE
PVC 245	PVC		35	53	2,5	47	75	
PVC COLOURS	PVC		35*	53	2,4	47	75	8 COLOURS**
PVC 243	EMBOSSED PVC		30	52	2,1	47	75	BROWN, TRANSPARENT AND WHITE
PVC 260	PVC		45	67	2,5	54	70	
PVC 270	PVC		58	81	2,5	60	70	

(\*) Thickness indicated for PVC RED, consult thicknesses for other colours.

(\*\*) Red, green, blue, white, orange, black, yellow, fluorescent orange.

PACKAGING

Polypropylene & polyethylene

Did you know this about our PP tapes ?

- They are **RECYCLABLE** by mechanical recycling or chemical recycling systems.
- PP tapes can be easily broken down and be used as an **ENERGY RECOVERY SOURCE**.
- The PP tapes adhesive is produced using natural rubber that is obtained from sustainably harvested “hevea brasiliensis” trees on plantations/farms.
- Around 98% of the solvent used is recovered and reused in the production process. This is achieved by using the Best Available Technology (BAT) for the sector in Europe.

PRODUCT	BACKING	ADHESIVE	BACKING THICKNESS (MIC)	TOTAL THICKNESS (MIC)	ADHESION (N/CM)	TENSILE STRENGTH (N/CM)	ELONGATION AT BREAK (%)	COLOUR
PP 5005	BOPP	HOT-MELT	25	41	5,2	38	150	BROWN, TRANSPARENT AND WHITE
PP 5120	BOPP		28	44	5,2	44	150	
PP 5130	BOPP		28	48	5,5	44	150	
PP 525	BOPP	NATURAL RUBBER	25	41	2,5	38	150	
PP 530	BOPP		28	43	2,5	44	150	
PP 532 <div>NEW</div>	BOPP		28	46	2,5	44	150	
PP 535 <div>NEW</div>	BOPP		30	45	2,5	48	150	
PP 540	BOPP		32	50	2,5	54	150	
PP 545 LN	BOPP		32	54	0,9	54	150	
PP 723 <div>NEW</div>	BOPP		23	38	2,3	38	150	
PE 725 <div>NEW</div>	PE		25	40	2,3	45	90	







# PACKAGING

## Kraft & paper tapes

Did you know this about our Kraft tapes and paper tapes?

- We have FSC®/PEFC certified paper tape versions.
- Paper backing is manufactured sustainably using elemental chlorine-free (ECF) materials in their manufacture.
- Kraft 700 and Kraft 7000 are recyclable or repulpable in the paper recovery process.



PRODUCT	BACKING	ADHESIVE	BACKING THICKNESS (MIC)	TOTAL THICKNESS (MIC)	ADHESION (N/CM)	TENSILE STRENGTH (N/CM)	COLOUR	PRODUCT CERTIFICATIONS
KRAFT 4800 / 4801	KRAFT PAPER	HOT-MELT	90	105	8	45	BROWN AND WHITE	-
CREPE 460	CREPED PAPER	NATURAL RUBBER	90	125	2,3	34	BROWN, IVORY, WHITE AND YELLOW	-
KRAFT 4850	REINFORCED KRAFT	HOT-MELT	200	240	>16	115	BROWN	 Promoting Sustainable Forest Management PEFC® C167528 www.pefc.org
<div>NEW</div> KRAFT 4855	REINFORCED KRAFT 50% RECYCLED	HOT-MELT	200	240	>16	115		
KRAFT 700*	RECYCLABLE PAPER	NATURAL RUBBER	100	120	2,5	54		 The mark of responsible forestry FSC® C167528
KRAFT 7000*		HOT-MELT	100	120	6,5	54		 The mark of responsible forestry FSC® C167528
<div>NEW</div> REINFORCED 7200	CREPED REINFORCED PAPER	HOT-MELT	90	135	7,0	80	BROWN AND WHITE	 The mark of responsible forestry FSC® C167528
<div>NEW</div> KRAFT 7250	REINFORCED KRAFT	HOT-MELT	100	160	10,0	165	BROWN	 The mark of responsible forestry FSC® C167528
<div>NEW</div> MASKING 7150	CREPED PAPER	HOT-MELT	90	110	5,5	50	BROWN AND WHITE	 The mark of responsible forestry FSC® C167528




(\*) Recyclable tapes.

# PACKAGING

## Printable tapes

Did you know this  
about our printable tapes?

- We have the biggest range of printable tapes.

PRODUCT	BACKING	ADHESIVE	BACKING THICKNESS (MIC)	TOTAL THICKNESS (MIC)	ADHESION (N/CM)	TENSILE STRENGTH (N/CM)	ELONGATION AT BREAK (%)	COLOUR	PRODUCT CERTIFICATIONS
PVC 240	PVC	NATURAL RUBBER	32	49	2,4	47	75	BROWN, TRANSPARENT AND WHITE	-
PVC 245	PVC		35	53	2,5	47	75		-
PVC COLOURS	PVC		35*	53	2,4	47	75	8 COLOURS**	-
PVC 243	EMBOSSED PVC		30	52	2,1	47	75	BROWN, TRANSPARENT AND WHITE	-
PVC 260	PVC		45	67	2,5	54	70		-
PVC 270	PVC		58	81	2,5	60	70		-
PP 569	BOPP		28	43	2,7	44	150		-
PP 570	BOPP		30	46	2,7	48	150		-
PP 572	BOPP		32	49	2,7	54	150		-
PP 726	BOPP		26	41	2,3	38	150		
PE 728	PE		25	40	2,3	45	90		
PP 6525	BOPP	HOT-MELT	25	42	5,2	38	150	-	
PP 6530	BOPP	HOT-MELT	28	44	5,2	44	150	-	
PP 6540	BOPP	HOT-MELT	40	61	5,5	65	160	-	
KRAFT 4800/4801	KRAFT PAPER	HOT-MELT	90	105	8	45	7	BROWN AND WHITE	-
CREPE 460	CREPED PAPER	NATURAL RUBBER	90	125	2,3	34	10	BROWN, IVORY, WHITE AND YELLOW	-
KRAFT 700	RECYCLABLE PAPER	NATURAL RUBBER	100	120	2,5	54	6	BROWN	
KRAFT 7000		HOT-MELT	100	120	6,5	54	6		
MASKING 7150	CREPED PAPER	HOT-MELT	90	110	5,5	50	10	BROWN AND WHITE	
REINFORCED 7200	CREPED REINFORCED PAPER	HOT-MELT	90	135	7,0	80	5		
KRAFT 7250	REINFORCED KRAFT	HOT-MELT	100	160	10,0	165	6	BROWN	

(\*) Thickness indicated for PVC RED, consult thicknesses for other colours.

(\*\*) Red, green, blue, white, orange, black, yellow, fluorescent orange.

# STRAPPING TAPES

And fiberglass filament

Launching for the first time a natural rubber solvent mopp strapping tape

- Valid for strapping applications even at refrigeration and freezing temperature working conditions. Also for holding of internal elements in white line goods during the transport and distribution.

PRODUCT	BACKING	ADHESIVE	TOTAL THICKNESS (MIC)	ADHESION (N/CM)	TENSILE STRENGTH (N/CM)	ELONGATION AT BREAK (%)	COLOUR	APPLICATIONS
REF. 8200	MONO	HOT-MELT	115	9,0	210	5	TRANSPARENT	BUNDLING, PALLETIZING AND REINFORCING
REF. 8050	CROSS	HOT-MELT	135	10,0	240	5		
REF. 8100	CROSS	HOT-MELT	130	12,0	280	5		
PP 5430	MOPP	HOT-MELT	72	6,0	150	35	ORANGE, WHITE, BLACK AND TRANSPARENT	BUNDLING, PALLETIZING, REINFORCING AND WHITE LINE INTERNAL ELEMENT HOLDING
PP 5440		HOT-MELT	97	6,5	260	35	BLACK AND TRANSPARENT	
PP 580		NATURAL RUBBER	72	2,7	150	35	ORANGE, BLUE, WHITE, BLACK AND TRANSPARENT	
PP 590		NATURAL RUBBER	97	2,7	260	35		

# DOUBLE SIDED TAPES

Our range of double sided adhesive tapes is expanding

- For a precise fixing, whether temporary or permanent, of anything you want to join together: carpets, textiles, plastics, paper, etc.



PRODUCT	BACKING	TOTAL THICKNESS (MIC)	ADHESION (N/CM)	TENSILE STRENGTH (N/CM)	APPLICATIONS
D.A. 1700	TISSUE	100	10	10	Diverse applications in the paper industry, textiles, affixing photographic enlargements, etc.
D.A. 2000	WHITE PP CAST	180	12	25	Positioning of rugs, affixing and splicing textiles and general assembly on rough surfaces.
D.A. 1030	COTTON CLOTH	260	9	28	
D.A. 1020	POLYESTER CLOTH	185	11	34	
D.A. 2050	BOPP	85	9	150	

# DUCT TAPES

Did you know this  
about our duct tapes?

- Introducing the chance to Single Wrap and Label our Duct Tapes.



PRODUCT	BACKING	ADHESIVE	BACKING THICKNESS (MIC)	TOTAL THICKNESS (MIC)	ADHESION (N/CM)	TENSILE STRENGTH (N/CM)	COLOUR	OUTDOOR
DUCT TAPE 6300	POLYETHYLENE AND POLYESTER	HOT-MELT	55	175	8	30	WHITE, GRAY AND BLACK	NO
DUCT TAPE 6500		HOT-MELT	55	190	9	35		NO
DUCT TAPE 6601		HOT-MELT	80	220	10	45	ORANGE, GRAY, YELLOW, BLUE AND RED	✓
DUCT TAPE 6605		HOT-MELT	80	220	14	45		✓

# MASKING

Did you know this about our masking tapes?

- We offer a wide range of masking tapes for all uses and applications: decoration, automotive, construction, etc.
- Paper backing is manufactured sustainably using elemental chlorine-free (ECF) materials in their manufacture.



PRODUCT	ADHESIVE	BACKING THICKNESS (MIC)	TOTAL THICKNESS (MIC)	ADHESION (N/CM)	TEMPERATURE RESISTANCE	WATER RESISTANCE	COLOUR
MASKING 460		90	125	2,3	60° / 1 hour		IVORY, BROWN AND YELLOW
MASKING 480		90	127	2,4	80° / 1 hour		YELLOW
MASKING 481		90	130	2,5	80° / 1 hour		IVORY, BROWN AND YELLOW
MASKING 482		90	130	2,5	80° / 1 hour		ORANGE
MASKING 483	NATURAL RUBBER	115	140	2,8	80° / 1 hour		
MASKING 484		80	110	2,6	80° / 1 hour		BLUE
MASKING 485		110	145	2,8	80° / 1 hour		ORANGE AND GREEN
MASKING 510		110	145	2,8	100° / 1 hour		
MASKING 4150	HOT-MELT	90	110	5,5	40° / 1 hour		IVORY



---

**CINTAS ADHESIVAS UBIS, S.A.**

Pol. Lastaola - Apartado 39  
20120 Hernani-España

Tel. [0034] 943 335 077  
Fax [0034] 943 332 580  
info@ubis.es

[www.ubis.es](http://www.ubis.es)

---



THIS CATALOGUE HAS BEEN PRINTED USING CERTIFIED ENVIRONMENTALLY FRIENDLY PAPER PRODUCED FROM SUSTAINABLY MANAGED FORESTS.