

8050 ECONOMY GRADE CROSS WEAVE FIBERGLASS FILAMENT TAPE

TYPICAL APPLICATIONS

Cross weave fiberglass filament tape suitable for reinforcing, bundling, palletizing and packing.

ADVANTAGES AND BENEFITS

- Second Excellent adhesion and tack.
- High tensile strength.

CONSTRUCTION

- Backing: Cross Weave fiberglass filament reinforced BOPP.
- Adhesive: Synthetic rubber and hydrocarbon resins transparent adhesive.





TECHNICAL DATA

8050	METRIC
Film Thickness	25 Micron
Total Thickness	120 Micron
Peel Adhesion	10 N/cm
Tensile Strength	240 N/cm
Elongation at break	5%



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.