CELOFAN 1600

CELLULOSE STATIONERY TAPE SUSTAINABLE PACKAGING

PEFC
PEFC/14-35-00522
PEFC Certified
CELOFAN 1600
www.pefc.org

TECHNICAL SHEET

Typical applications

- General purpose stationary tape.
- Sustainable tape for light and medium weight packaging.

EXCELLENT ADHESION

HOT MELT

Ventajas y beneficios

- **100% PEFC certificated adhesive tape.**
- Excellent adhesión.
- Good tack.
- Long lasting adhesion.
- Hand tearable.

Construction

- Backing: 100% PEFC Certified cellulose based film.
- Adhesive: Synthetic rubber and hydrocarbon resins.
- Transparent adhesive.
- Color: Transparent.

Technical data

CELLULOSE 1600	METRIC
Film Thickness	28 Micron
Total Thickness	44 Micron
Peel Adhesion	6 N/cm
Tensile Strength	35 N/cm
Elongation at break	20 %

AENOR Registered Company ISO 9001

AENOR Environmental Management ISO 14001

Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

Storage

El rendimiento de la cinta está garantizado dentro de los primeros 12 meses desde su fabricación. El producto debe mantenerse en su caja original y en un ambiente seco y alejado de la luz solar directa. Para la trazabilidad del producto, deberá indicarse el lote de fabricación impreso en la caja del producto.

Secutiry

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.

CINTAS ADHESIVAS UBIS S.A. / Polígono Industrial Lastaola · Apartado 39 · 20120 Hernani · Guipúzcoa · Spain / T. (+34) 943 335 077 · E. Info@ubis.es / www.ubis.es