

TECHNICAL SHEET

TYPICAL APPLICATIONS

- 🔗 Masking paper tape suitable for a **sustainable** packaging or painting jobs.
- 🔗 Light and medium weight packaging sealing tape.
- 🔗 Suitable either with a manual dispenser or automated application.
- 🔗 Utility grade masking tape, used on a variety of surfaces for general purpose masking.
- 🔗 Miscellaneous industrial applications

ADVANTAGES AND BENEFITS

- 🔗 FSC® MIX AEN-COC-000330 certified adhesive tape.
- 🔗 Excellent adhesion to all surfaces.
- 🔗 **Directly printable** by flexographic printing method.
- 🔗 Paper manufactured from unbleached Elementary Chlorine Free (ECF) natural pulp.

CONSTRUCTION

- 🔗 Backing: Premium FSC® certified masking paper.
- 🔗 Adhesive: synthetic **rubber**.
- 🔗 Available in brown and white.



TECHNICAL DATA

<i>KRAFT 7150</i>	<i>METRIC</i>
Paper Thickness	90 Micron
Paper Weight	60 g/m²
Total Thickness	110 Micron
Peel Adhesion	5,5 N/cm
Tensile Strength	50 N/cm
Elongation at Break	10 %
Service Temperature	-10°C / +50°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 6 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.