

## TECHNICAL SHEET

### TYPICAL APPLICATIONS

- Masking paper tape suitable for a **sustainable** packaging or painting jobs.
- Light and medium weight packaging sealing tape.
- Suitable either with a manual dispenser or automated application.
- Utility grade masking tape, used on a variety of surfaces for general purpose masking.
- Miscellaneous industrial applications

### ADVANTAGES AND BENEFITS

- FSC® MIX AEN-COC-000330 certified adhesive tape.
- Excellent adhesion to all surfaces.
- Directly printable** by flexographic printing method.
- Paper manufactured from unbleached Elementary Chlorine Free (ECF) natural pulp.

### CONSTRUCTION

- Backing: Premium **FSC®** certified masking paper.
- Adhesive: synthetic **rubber**.
- Available in brown and white.



### TECHNICAL DATA

<i>MASKING 7150</i>	<i>METRIC</i>
Paper Thickness	90 Micron
Paper Weight	60 g/m <sup>2</sup>
Total Thickness	110 Micron
Peel Adhesion	5,5 N/cm
Tensile Strength	50 N/cm
Elongation at Break	10 %
Service Temperature	-10°C / +50°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

### STORAGE

Tape performance is guaranteed within the first 6 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

### SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.