

### TECHNICAL SHEET

#### TYPICAL APPLICATIONS

- Double Sided tape suitable for permanent or temporary carpet laying preparation at exhibitions and domestic applications. Also for miscellaneous industrial splicing and mounting applications.



#### ADVANTAGES AND BENEFITS

- Excellent adhesion to all surfaces.
- Good adaptability on different surfaces and shapes.
- Easy and clean removal.
- Hand tearable.

#### CONSTRUCTION

- Backing: polyester cloth with bisilicone paper liner.
- Adhesive: Synthetic rubber and hydrocarbon resins. White colour.



#### TECHNICAL DATA

DA1020	METRIC
Polyester cloth thickness	140 Micron
Bisilicone paper thickness	65 Micron
Total Thickness (Adhesive+cloth)	185 Micron
Adhesive Weight	160 g/m <sup>2</sup>
Peel Adhesion	11,5 N/cm



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

#### STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

#### SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.