

TECHNICAL SHEET

TYPICAL APPLICATIONS

- Double Sided tape suitable for permanent or temporary carpet laying preparation at exhibitions and domestic applications. Also for miscellaneous industrial splicing and mounting applications.



ADVANTAGES AND BENEFITS

- Excellent adhesion to all surfaces.
- Good adaptability on different surfaces and shapes.
- Easy and clean removal.
- Hand tearable.

CONSTRUCTION

- Backing: White cast PP with bisilicone paper liner.
- Adhesive: Synthetic rubber and hydrocarbon resins. Transparent colour



TECHNICAL DATA

| DA2000 | METRIC |
|-------------------------------|----------------------|
| Film thickness | 73 Micron |
| Bisilicone paper thickness | 65 Micron |
| Total Thickness (Adhesive+PP) | 180 Micron |
| Adhesive Weight | 110 g/m ² |
| Peel Adhesion | 12,5 N/cm |



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.