

TECHNICAL SHEET

TYPICAL APPLICATIONS

- Double Sided tape suitable for lightweight mounting, fixing, laminating, assembling photos, sample displays, etc. Also Economy carpet fixing.



ADVANTAGES AND BENEFITS

- Excellent adhesion to all surfaces.
- Good adaptability on different surfaces and shapes.
- Hand tearable.

CONSTRUCTION

- Backing: Transparent BOPP with bisilicone paper liner.
- Adhesive: Synthetic rubber and hydrocarbon resins.
- White and transparent colors available.



TECHNICAL DATA

DA2050	METRIC
Film thickness	25 Micron
Bisilicone paper thickness	65 Micron
Total Thickness (Adhesive+PP)	85 Micron
Adhesive Weight	60 g/m ²
Peel Adhesion	9 N/cm



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.