

### TECHNICAL SHEET

#### TYPICAL APPLICATIONS

- ☞ Kraft paper carton sealing tape suitable for manual and automated application.



#### ADVANTAGES AND BENEFITS

- ☞ Excellent adhesion even in recycled cartons.
- ☞ Good tack.
- ☞ Printable.
- ☞ Hand tearable.

#### CONSTRUCTION

- ☞ Backing: Kraft paper
- ☞ Adhesive: Synthetic rubber and hydrocarbon resins.
- ☞ Colour: Brown.



#### TECHNICAL DATA

	METRIC
Paper Thickness	90 Micron
Total Thickness	110 Micron
Peel Adhesion	8,5 N/cm
Tensile Strength	45 N/cm
Holding Power to Kraft @ 50°C in oven	100 hours
Application Temperature	6°C to 45°C
Service Temperature	-10°C to 60°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

#### STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

#### SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.