

TECHNICAL DATA SHEET

Typical applications

Fiber-glass reinforced paper tape for a secure packaging.
 Suitable either for manual application or automated packaging systems.
 Suitable for heavy duty packaging.
 Specially designed to be used on the **e-commerce**.



Advantages and benefits

100% PEFC certified adhesive tape.
 Paper comes from certified sustainable sources.
 Extreme adhesion power to all surfaces, including the recycled cardboard.
 The tape protects the packaging content working as a temper evident seal.
 Easy to apply with conventional manual tape dispensers anywhere and on any surface.



Construction

Backing: Fiber-glass reinforced 100% PEFC certified paper.
 The tape core is made from 100% recycled material.
 Adhesive: Synthetic rubber. Special formula for an extreme peel and adhesion power.
 Colour: brown.

Technical data

KRAFT 4850	METRIC
Backing thickness	200 Micron
Total thickness	240 Micron
Peel adhesion	> 16 N/cm
Tensile strength	115 N/cm
Elongation at break	6 %
Service temperature	-10°C / +60°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

Storage

Tape performance is guaranteed within the first 6 months. Product must be kept in its original packaging and in a dry atmosphere away from direct sunlight. For product traceability, the production batch number on the box of the product has to be indicated.

Safety

Product does not contain any dangerous or unhealthy components. Safety data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.