

TECHNICAL SHEET

TYPICAL APPLICATIONS

- 🔗 Certified kraft paper backing suitable for a **sustainable** packaging.
- 🔗 Backing reinforced with uniaxially oriented **fiberglass**.
- 🔗 Medium and heavy duty carton sealing tape.
- 🔗 Designed to make safe shipments through the **e-commerce**.
- 🔗 Suitable either with a manual dispenser or automated application.



ADVANTAGES AND BENEFITS

- 🔗 FSC® MIX AEN-COC-000330 certified adhesive tape.
- 🔗 Excellent adhesion to all surfaces.
- 🔗 **Directly printable** by flexographic printing method.
- 🔗 Paper manufactured from unbleached Elementary Chlorine Free (ECF) natural pulp.



CONSTRUCTION

- 🔗 Backing: Premium FSC® certified Kraft paper.
- 🔗 Adhesive: synthetic **rubber**.
- 🔗 Reinforcement: uniaxially oriented fiberglass.
- 🔗 The **tape core** is made from 100% recycled material.
- 🔗 Available in brown color.

TECHNICAL DATA

<i>KRAFT 7250 FSC®</i>	<i>METRIC</i>
Paper Thickness	100 Micron
Paper Weight	70 g/m ²
Total Thickness	160 Micron
Peel Adhesion	10,0 N/cm
Tensile Strength	165 N/cm
Elongation at Break	6 %
Service Temperature	-10°C / +50°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 6 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12-digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.