

TECHNICAL SHEET

TYPICAL APPLICATIONS

- Utility grade masking tape, used on a variety of surfaces for general purpose masking, packaging, bundling, sealing, splicing and miscellaneous industrial applications.



ADVANTAGES AND BENEFITS

- Excellent adhesion to all surfaces.
- Easy application on curved profiles and irregular surfaces.
- Easy removal with no residue if removed as paint is dry.
- Compatible with solvent based paints and most water based paints.
- Note: This tape is not designed for oven baking.**

CONSTRUCTION

- Backing: Saturated crepe paper.
- Adhesive: Synthetic rubber and hydrocarbon resins.
- Color: Ivory.



TECHNICAL DATA

MASKING 4150	METRIC
Paper Thickness	90 Micron
Total Thickness	110 Micron
Peel Adhesion	5,5 N/cm
Tensile Strength	34 N/cm
Elongation at break	10%



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 6 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.