


### TECHNICAL SHEET

#### TYPICAL APPLICATIONS

- Masking tape suitable for wall painting and miscellaneous industrial painting applications .



#### ADVANTAGES AND BENEFITS

- Good adhesion to all surfaces.
- Easy application on curved profiles and irregular surfaces.
- Easy removal.
- No residue.
- Compatible with water based and solvent paints.
- 60°C 1 hour temperature service

#### CONSTRUCTION

- Backing: Saturated crepe paper.
- Adhesive: Natural rubber and hydrocarbon resins.
- Color: Yellow.



#### TECHNICAL DATA

MASKING 461	METRIC
Paper Thickness	90 Micron
Total Thickness	125 Micron
Peel Adhesion	2,5 N/cm
Tensile Strength	34 N/cm
Elongation at break	10%
Temperature resistance	60°C 1 hour



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

#### STORAGE

Tape performance is guaranteed within the first 6 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

#### SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.