



MASKING 495

STRONG WATER REPELENT AUTOMOTIVE MASKING TAPE

TECHNICAL SHEET

TYPICAL APPLICATIONS

- Masking tape suitable for 80°C 1 hour oven baking in car body shops.
- Suitable for miscellaneous industrial, construction and other painting applications.



ADVANTAGES AND BENEFITS

- Premium Strong Water Repellent paper.
- Excellent adhesion to all surfaces.
- Easy application on curved profiles and irregular surfaces.
- No residue after easy removal.
- Compatible with solvent-based paints and water-based paints.
- 80°C 1 hour temperature service.



CONSTRUCTION

- Backing: Saturated Strong Water Repellent crepe paper.
- Adhesive: Natural rubber and hydrocarbon resins.
- Available Color: Fluor yellow.

TECHNICAL DATA

MASKING 795	METRIC	METHOD
Paper Weight	60 g/m ²	-
Total Thickness	130 Micron	AFERA 5006
Peel Adhesion	2,5 N/cm	AFERA 5001
Tensile Strength	33 N/cm	AFERA 5004
Elongation at break	10 %	AFERA 5004
Temperature resistance	80°C 1 hour	-



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 6 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the full digit batch number printed on the labels of the packaging.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.