

## **PE 725** POLYETHYLENE TAPE WITH 100% RECYCLED FILM\* ISCC PLUS CERTIFIED



| POLYETHYLENE 725    | METRIC        | TEST METHOD |
|---------------------|---------------|-------------|
| Backing thickness   | 25 Micron     | AFERA 5006  |
| Total thickness     | 40 Micron     | AFERA 5006  |
| Peel adhesion       | 2,3 N/cm      | AFERA 5001  |
| Tensile strength    | 45 N/cm       | AFERA 5004  |
| Elongation at break | 90 %          | AFERA 5004  |
| Service temperature | -35°C / +65°C | -           |

| AENOR                 | AENOR                       |  |
|-----------------------|-----------------------------|--|
| QUALITY<br>MANAGEMENT | ENVIRONMENTAL<br>MANAGEMENT |  |
| 150 9001              | 150 14001                   |  |

Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application. With every PE 725 tape order, Ubis will issue a specific sustainability declaration to certify the recycled material content and origin.

## Storage:

Tape performance is guaranteed within the first 6 months. Product must be kept in its original packaging and in a dry atmosphere away from direct sunlight. For product traceability, the production batch number on the box of the product has to be indicated.

## Safety:

Product does not contain any dangerous or unhealthy components. Safety data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.

CINTAS ADHESIVAS UBIS S.A. / Polígono Industrial Lastaola · Apartado 39 · 20120 Hernani · Guipúzcoa · Spain / T. (+34) 943 335 077 · E. Info@ubis.es / www.ubis.es