



PP 5130

PREMIUM GRADE CARTON SEALING BOPP TAPE

TECHNICAL SHEET

TYPICAL APPLICATIONS

- Heavy weight carton sealing tape suitable for manual dispenser application. Also for automated application.



ADVANTAGES AND BENEFITS

- Excellent adhesion even in recycled cartons.
- Good tack.
- The adhesive high holding power value guarantees a long lasting adhesion and a safe storage even with temperature variations.

CONSTRUCTION

- Backing: Biaxially oriented polypropylene clear film.
- Adhesive: Synthetic rubber and hydrocarbon resins.
- Colour: Clear, white or brown adhesive.



TECHNICAL DATA

PP5130	METRIC
Film Thickness	28 Micron
Total Thickness	49 Micron
Peel Adhesion	5,5 N/cm
Tensile Strength	45 N/cm
Elongation at break	120%
Holding power to Kraft paper @ 50°C in oven	15 hours
Application Temperature	6°C to 45°C
Service Temperature	-10°C to 60°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.