

TECHNICAL SHEET

TYPICAL APPLICATIONS

- Easy direct printable carton sealing tape.
- Ideal for manual or automated applications.



ADVANTAGES AND BENEFITS

- Specially treated outside surface which allows a superior quality printability.
- Printable with polyamide inks (no need primer and release)
- Easy unwind and fast printability.
- Excellent adhesion even in recycled cartons.
- Excellent tack.
- Long lasting adhesion.
- Ideal for storage in extreme temperature conditions and high moisture environments once applied.



CONSTRUCTION

- Backing: Clear BOPP film.
- Adhesive: Natural rubber and hydrocarbon resins.
- Colour: Clear, white or brown adhesive.

TECHNICAL DATA

PP 569	METRIC
Film Thickness	28 Micron
Total Thickness	44 Micron
Peel Adhesion	2 N/cm
Tensile Strength	40 N/cm
Elongation at break	120%
Application Temperature	2°C to 45°C
Service Temperature	-25°C to 65°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.