

TECHNICAL SHEET

TYPICAL APPLICATIONS

- Printable carton sealing PVC tape, suitable for manual dispenser application.

ADVANTAGES AND BENEFITS

- Ultra White colour due to a special film treatment.
- Good adhesion even in recycled cartons.
- Excellent tack.
- Long lasting adhesion.
- No noise, silent unwinding.
- Printable with vinyl inks.
- Easy unwind and fast printability.
- Ideal for storage in extreme temperature conditions and high moisture environments once applied.

CONSTRUCTION

- Backing: Unplastified clear PVC film.
- Adhesive: Natural rubber and hydrocarbon resins.
- Colour: Ultra White.



TECHNICAL DATA (This Grade is only available in white colour)

	METRIC
Film Thickness	35 Micron
Total Thickness	54 Micron
Peel Adhesion	2,6 N/cm
Tensile Strength	47 N/cm
Elongation at break	60%
Application Temperature	10°C to 45°C
Service Temperature	-25°C to 65°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.