

## TECHNICAL SHEET

### TYPICAL APPLICATIONS

- 9 Certified paper backing suitable for a **sustainable** packaging.
- 9 Backing reinforced with uniaxially oriented **fiberglass**.
- 9 Medium and heavy-duty carton sealing tape.
- 9 Designed to make safe shipments through the **e-commerce**.
- 9 Suitable either with a manual dispenser or automated application.



### ADVANTAGES AND BENEFITS

- 9 FSC® MIX AEN-COC-000330 certified adhesive tape.
- 9 Excellent adhesion to all surfaces.
- 9 **Directly printable** by flexographic printing method.
- 9 Paper manufactured from unbleached Elementary Chlorine Free (ECF) natural pulp.



### CONSTRUCTION

- 9 Backing: **FSC®** certified paper.
- 9 Adhesive: synthetic **rubber**.
- 9 Reinforcement: uniaxially oriented fiberglass.
- 9 The tape core is made from 100% recycled material.
- 9 Available in white and brown colors.

### TECHNICAL DATA

REINFORCED 7200 FSC®	METRIC
Paper Thickness	90 Micron
Paper Weight	60 g/m <sup>2</sup>
Total Thickness	135 Micron
Peel Adhesion	7,0 N/cm
Tensile Strength	80 N/cm
Elongation at Break	5 %
Service Temperature	-10°C / +60°C



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

### STORAGE

Tape performance is guaranteed within the first 6 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12-digit batch number printed on labels.

### SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.