

### TECHNICAL SHEET

#### TYPICAL APPLICATIONS

- General purpose tape suitable for bundling, sealing, seaming, repairing, holding, plumbing and waterproofing.



#### ADVANTAGES AND BENEFITS

- Excellent adhesion and conformability.
- Excellent tack.
- Long lasting adhesion.
- Waterproof backing
- Hand tear able.
- Clean removal after 5 days outdoor

#### CONSTRUCTION

- Backing: Polyethylene reinforced with polyester cloth.
- Adhesive: Synthetic rubber and hydrocarbon resins.
- clear adhesive
- Orange or Silver color coextruded polyethylene on open side and white on reverse side



#### TECHNICAL DATA

6500	METRIC
Film Thickness	80 Micron
Total Thickness	220 Micron
Peel Adhesion	12 N/cm
Tensile Strength	45 N/cm
Elongation at break	20%



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

#### STORAGE

Tape performance is guaranteed within the first 12 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

#### SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.