




MASKING 483 ORANGE

SUPERIOR ADHESION PREMIUM AUTOMOTIVE MASKING TAPE

TECHNICAL SHEET

TYPICAL APPLICATIONS

- Masking tape suitable for 80°C 1 hour oven baking in car body shops.



ADVANTAGES AND BENEFITS

- Excellent adhesion to all surfaces.
- Excellent adhesion to paper back side.
- Easy application on curved profiles and irregular surfaces.
- Easy removal.
- No residue.
- Compatible with solvent based paints and most water based paints.
- 80°C 1 hour temperature service.



CONSTRUCTION

- Backing: Saturated coarse crepe paper.
- Adhesive: Natural rubber
- Color: Orange.
- Other colors also available for big quantities.

TECHNICAL DATA

MASKING 483	METRIC
Paper Weight	60 Gsm.
Total Thickness	140 Micron
Peel Adhesion	2,7 N/cm
Tensile Strength	35 N/cm
Elongation at break	8%
Temperature resistance	80°C 1 hour



Physical and performance characteristics shown above are obtained following tests recommended by AFERA and UBIS. The values given are typical values and do not constitute a specification. The user should determine whether the tape is suitable for the intended application.

STORAGE

Tape performance is guaranteed within the first 6 months. Product must be kept in its original box and in a dry atmosphere away from direct sunlight. For product traceability, please advise the 12 digit batch number printed on labels.

SECURITY

Product does not contain any dangerous or unhealthy components. Security data sheets are available based on directive 91/155/EC. All our tapes comply with European 2004/12/CE Packaging directive.